



## Performance levels in a modern design product

Q3X is the ideal solution for those customers searching for the latest performance levels in a modern design product. The thermal head provides excellent graphic printing quality and lower consumption. The cutter has been designed to optimize the product performance, both in terms of efficiency and reliability, and meets the most demanding operating requirements. Its elegant design, developed to perfectly match any environment, is combined with high technological contents. It prints on 80 mm wide thermal paper, with front ticket outlet. Serial / USB interface. Bluetooth and Wi-Fi interfaces available.









## **TECHNICAL SHEET**

|                    | Q3X   | Q3X Wi-Fi       | Q3X Bluetooth       | Q3X Ethernet |
|--------------------|---|-----------------|---------------------|--------------|
| Interfaces         | RS232+USB   | RS232+USB+WI-FI | RS232+USB+Bluetooth | Ethernet     |
| Printing Method    | Thermal printing  |                 |                     |              |
| Number of dots     | 8 dots / mm   |                 |                     |              |
| Resolution         | 203 DPI   |                 |                     |              |
| Printing (mm/sec)  | 140   |                 |                     |              |
| Character set      | PC437, PC850, PC860, PC863, PC865, PC858 (euro)   |                 |                     |              |
| Printing Format    | Normal, height and width from 1x to 8x, reverse, underlined, script, bold   |                 |                     |              |
| Printing Direction | Straight 90°, 180°, 270°  |                 |                     |              |
| Paper width        | 80 mm   |                 |                     |              |
| Paper weight       | 55 gr/m <sup>2</sup>  |                 |                     |              |
| Paper thickness    | 61 Mm   |                 |                     |              |
| Roll Dimension     | max diam. 80 mm   |                 |                     |              |
| Emulation          | CUSTOM / POS  |                 |                     |              |
| Data Buffer        | 20 KB   |                 |                     |              |
| Flash Memory       | 4 MB  |                 |                     |              |
| Graphic Memory     | 1 logo (576x910 dots)   |                 |                     |              |
| Drivers            | (Windows WHQL certified): WindowsTM XP, 2K3, Vista, W7, W8 (+64bit support), W10, Linux (32/64 bit), OPOS, JavaPOS, MAC OSX |                 |                     |              |
| Power supply       | 24 Vdc ± 10% (External power supply)  |                 |                     |              |
| Medium consumption | 1.5 A (50% printing rat   | e)              |                     |              |
| DKD Function       | 1 Drawer kickout  |                 |                     |              |
| MTBF               | 360,000 hours (electronic board)  |                 |                     |              |
| Safety             | EN60950 +A1+A2+A3+A4  |                 |                     |              |
| Marks              | CE, RoHS Compliant  |                 |                     |              |
| Dimensions         | 150 mm (L) × 140 mm (W) × 117mm (H)   |                 |                     |              |
| Weight             | 0.9 Kg  |                 |                     |              |












## **MODELS**











911FF010100333 PRINTER Q3X USB RS232 BLACK





911FF010200B33 PRINTER Q3X WIFI USB RS232 BLACK





911FF010100533 PRINTER Q3X ETH

CUSTOM SPA - Via Berettine, 2 - 43010 Fontevivo PR - VAT: IT02498250345 - TEL: +39 0521 680111 - FAX: +39 0521 610701 - UNIQUE CODE: TI80WI0

The technical data on this website are not binding and may be changed without advanced notice. Last update: 19 December 2019





