



1004L 10.1-inch LCD

Touchscreen Monitor



**Optically-bonded
Display**



**IP54 & IK07
Protection**



**Edge-to-edge glass
with integrated 10-touch**

Product Overview

The Elo 1004L 10.1-inch touchscreen monitor combines reliable performance, precise touch, and a compact design built for commercial environments. Powered by TouchPro® PCAP technology, it delivers fast, accurate response with up to 10 simultaneous touches, enhanced by optical bonding for improved clarity and durability and an IP54-sealed design for protection against dust and spills in high-use settings.

With a slim profile, flexible mounting options, and support for USB-C, HDMI, and DisplayPort, the 1004L is easy to deploy and integrate across systems, supporting applications from point-of-sale and self-service kiosks to kitchen display systems and HMI.

Elo Edge Connect™ compatibility for payment devices, scanners, cameras, RFID, status lights and more

Create a sleek POS stack with the 1004L and Elo Pay 7", powered by a single USB-C connection

IEC 60601 certified for healthcare applications with flexible USB-C or AC/DC power options

Anti-glare surface provides added durability to withstand the rigors of continuous public use

1004L 10.1-inch LED Touchscreen Monitor

Specifications	
Model	1004L
Color	Black or White
Diagonal Size	10.1" / 256.54 mm
Active Display Area	8.54" x 5.34" / 216.96 x 135.6 mm
LCD Technology	Active matrix TFT LCD
Native Resolution	1280 x 800
Other Supported Resolutions	640x480 60Hz; 800x500 60Hz; 800x600 60Hz; 1024x768 60Hz; 1280x720 60Hz; 1280x800 60Hz, 60Hz RB; 1920x1080 60Hz; 1920x1200 60Hz
Aspect Ratio	16:10
Number of Colors	16.7M
Touch Technology	TouchPro PCAP, Non-touch
Number of Touches	10-touch (Touch function not available for non-touch model)
Brightness (typical)	Panel: 400 nits; With PCAP: 360 nits
Response Time (Tr + Tf) (Typical)	30 ms
Viewing Angle (typical)	Horizontal: 85°/85° or 170° total; Vertical: 85°/85° or 170° total
Contrast Ratio (typical)	800:1
On-Screen Display (OSD)	Accessible through touch OSD, and press Menu button to pop up touch OSD diagram. Controls (Touch Model): Menu, Power Controls (Non-Touch Model): Two keys (one power key + 5 directional key) Settings: Brightness, Contrast, Aspect Ratio, Auto Scan, Sharpness, Color Temperature, Low Blue Light, Volume, Mute, OSD Timeout, OSD Language, Touch on Sleep mode ON/OFF, Power LED ON/OFF, Recall Defaults, Peripheral Port Languages: English, French, Germany, Italian, Spanish, Japanese, Traditional Chinese, Simplified Chinese Lockouts: OSD, Power
I/O Ports	USB Type-C, Mini-Displayport, HDMI, DC jack, 4x Micro-USB Elo Edge Connect Ports
Video	USB Type-C, Mini-Displayport, HDMI Input Video Horizontal Sync frequency range: 30 - 82KHz; Input Video Vertical Sync (frame rate) frequency range: 60Hz Suggest using Elo USB Type C (Elo P/N: E129019) to prevent any compatibility issues
Power	Power Delivery compatible via USB Type-C connector or DC Jack (2.0mm pin outer diameter, 6.4mm barrel inner diameter)
Power Consumption (Typical)	ON (Default - 100% Brightness): 6.5W; SLEEP (Touch Model): 1.0W; SLEEP (Non -Touch Model): 0.5W; OFF: 0.25 W
Speakers	2 x 2W (+/-10%) internal speakers
Weight	Unpackaged: 1.98 lbs / 0.90 kg; Packaged: 4.84 lbs / 2.2 kg
Dimensions	9.80" x 6.61" x 0.98" / 249 mm x 168 mm x 25 mm
Shipping Dimensions	12.13" x 5.63" x 8.78" / 308 mm x 143 mm x 223 mm
Mounting Options	VESA 4-hole 75mm mounting interface on rear of unit
Temperature	Operating: 0 °C to 40 °C /32 °F to 104 °F; Storage: -20 °C to 60 °C /-4 °F to 140 °F
Humidity (non-condensing)	Operating: 20%-80%; Storage: 10%-95% (38.7° max wet bulb temperature)
Regulatory Approvals and Declarations	Argentina AR certificate; Canada CUL, IC; China CCC; Europe CE; Korea KCC; Taiwan BSMI; United States FCC, UL; Japan VCCI, PSE; International CB; Australia RCM; Mexico NOM; RoHS, China RoHS, WEEE, REACH; India BIS; United Kingdom UKCA
Healthcare Safety Standards	IEC60601 (with optional medical power brick kit - E181106) AAMI ES60601-1:2005/(R)2012 and A1:2012/(R)2012 and A2:2021 EN 60601-1:2006, EN 60601-1:2006/A1:2013, EN 60601-1:2006/A12:2014, EN 60601-1:2006/A2:2021 CAN/CSA-C22.2 No. 60601-1:14 (Reaffirmed 2022)
Ingress Protection	IP54
Impact Protection	IK07
Other Features	TUV Rhineland (Low Blue Light); Power collection function via DDCCI; PD (power delivery) out via USB-C (18W Max) for Elo Pay 7"
Warranty	3 years standard
Extended Warranty	4 year warranty - Elo P/N: E898247; 5 year warranty - Elo P/N: E898449 3 year warranty + AUR - Elo P/N: E898648; 4 year warranty + AUR - Elo P/N: E894921; 5 year warranty + AUR - Elo P/N: E895125
MTBF	50,000 hours demonstrated
What's in the Box	Touch Monitor, Quick Install Guide, EU EEI Label, 2x UK EEI Label, 1.8m USB-A to C Cable, 1.8m HDMI Cable, Power Brick, 1.8m NA Power Cable, 1.8m EU Power Cable, 2x Cable tie

Medical and Healthcare Application Disclaimer: It is the sole responsibility of any person intending to commercialize, market or use any of Elo Touch Solutions, Inc. or its family of companies ("Elo") products for medical or healthcare applications to ensure that such product is adequate and appropriate for the person's intended use and complies with all applicable laws, regulations, codes and standards including but not limited to the European Union Medical Device Directive, United States Federal Food, Drug, and Cosmetic Act, regulations of the United States Food and Drug Administration (FDA), and other similar legislation in jurisdictions around the world, and for obtaining and maintaining any required regulatory approvals including but not limited to any required market clearances. Elo has not sought nor received any rulings from the FDA or any other federal, state, or local government agency or notified body as to the safety, effectiveness or appropriateness of its product for such applications. Persons intending to evaluate or use Elo's product(s) for medical or healthcare purposes must rely on their own medical and legal judgment without any representation on the part of Elo.

Ordering Information

Part Number	Touch Technology	Mount	Interface	Surface Treatment	Color
E315290	Non-touch	No Stand	USB	Anti-glare	Black
E968703	Projected Capacitive	No Stand	USB	Anti-glare	Black
E616302	Non-touch	No Stand	USB	Anti-glare	White
E616491	Projected Capacitive	No Stand	USB	Anti-glare	White

Learn more about Elo at [EloTouch.com](https://www.elotouch.com).

Americas

Tel +1 408 597 8000
elosales.na@elotouch.com

Europe (EMEA)

Tel +32 16 930 136
EMEA.Sales@elotouch.com

Asia Pacific

Tel +86 (21) 3329 1385
www.elotouch.com.cn

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo and the Elo logo are trademarks of Elo Touch Solutions, Inc., registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners. © 2026 Elo Touch Solutions, Inc. All rights reserved. 26043AES00209

