

# MAGELLAN™ 3600VSi

 DATALOGIC

Smart. Fast. Green. One scan does it all.



## REINVENTING THE SPEED OF RETAIL

Datalogic's new 3600VSi series continues our legacy of innovation with industry-leading performance designed for today's fast-paced retail environments. Engineered for speed, accuracy, and reliability, the 3600VSi delivers exceptional scanning across 1D and 2D barcodes, including printed, mobile, damaged, or hard-to-read codes. With enhanced throughput and motion tolerance, checkout associates and shoppers alike enjoy a seamless, efficient experience every time.

Stay ahead of the curve with scanners built to support the latest standards including GS1 Digital Link, Digimarc, composite codes, and OCR. Unlock powerful capabilities like tracking expiration dates, managing recalls, and delivering personalized promotions, all through enhanced GS1 Digital Link data. With a low power consumption of 1.8 W, TUV certified 85% recycle plastics and eco-friendly packaging, it's the greenest Single Plane in the market.

## SMART SECURITY. SEAMLESS TRACKING.

Empower your point of sale with advanced features designed to protect your business and streamline operations. Enable loss prevention with RFID and EAS to track and deactivate items through checkout and returns. Unlock more capability with the 1 MP Color Video camera for recording security footage or couple with external AI applications for loss prevention or item recognition. Secure loyalty card processing with on-glass color image capture, and manage access with age verification from scanned IDs, all seamlessly integrated into your workflow.

## EMPOWERING YOUR WORKFLOW POTENTIAL

Take control of your retail ecosystem with remote capabilities for software updates, device diagnostics, and enterprise-level tracking, all powered by our advanced IoT platform. Effortlessly connect across Windows, Linux, or Android environments using OPOS, JavaPOS, or the Android SDK. Configure scanners with ease using Aladdin, giving you full flexibility and control.

## FEATURES

- Advanced digital imaging provides class-leading performance and reliability
- Seamless 1D, 2D, GS1 Digital Link, OCR, and Digimarc® digital watermark reading
- Smoothly reads all bar codes, whether displayed on cell phones or printed
- Subtle, adaptive illumination for user comfort
- Solid-state electronics for silent operation and superior reliability
- Software driven - flexible and upgradeable
- Read and write UHF RFID Tags
- Color video and color image capture
- USB-C power delivery
- Multiple interfaces in every unit
- Powered USB auxiliary port
- Checkpoint Systems and Tyco Sensormatic EAS compatible
- Cable retention harness
- IoT Remote Management Platform for diagnostics, SW upgrades, and configuration
- Available Magellan Customer Service Scanner (CSS) with omni-mount for reading cell phones, coupons and loyalty cards
- EASEOFCARE Service Plans offer a wide range of service options to protect your investment, ensuring maximum productivity and ROI

## INDUSTRY - APPLICATION

**Retail:** Convenience, Grocery, Discount, Specialty, Hardware, Fashion, Pharmacy, Hospitality

**Applications:** Attended POS, Self-Checkout POS, Kiosks, Ticketing, Access Control, Price Verification, Loss Prevention, ID Verification, Age Verification, Security Monitoring, Ticket Switching, EAS Deactivation, RFID Tracking, Sorting, Quality Assurance



## TECHNICAL SPECIFICATIONS

DECODING CAPABILITY		READING RANGES	
<b>1D / Linear Codes</b>	Autodiscriminates all standard 1D codes including GS1 DataBar™ linear codes.	Printing resolution, symbol length, scan angle, contrast and ambient light dependent. Distances measured from the product window.	
<b>2D Codes</b>	Aztec Code; Data Matrix (ECC200 only); QR Code	1D Codes 5 mils (Code39): 1 to 13cm / 0.5 to 5.0 in 7.5 mils (Code39): 0 to 18cm / 0 to 7.0 in 10 mils (EAN): 0 to 19cm / 0 to 7.5 in 13 mils (EAN): 0 to 22cm / 0 to 8.7 in 20 mils (Code39): 0 to 26cm / 0 to 10.0 in	
<b>Stacked Codes</b>	GS1 Digital Link, GS1 DataBar Composites; GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional; MicroPDF417; PDF417	2D Codes 6.6 mils (PDF): 1 to 12cm / 0.5 to 4.7 in 10 mils (PDF): 0 to 18cm / 0 to 7.0 in 10 mils (DM): 1 to 9cm / 0.5 to 3.5 in 15 mils (DM): 0 to 16cm / 0 to 6.3 in 15 mils (QR): 0 to 16cm / 0 to 6.3 in 20 mils (DM): 0 to 18cm / 0 to 7.0 in 20 mils (QR): 0 to 18cm / 0 to 7.0 in	
<b>Digital Watermarks</b>	Digimarc® Barcodes/GS1 DW Code		
ELECTRICAL			
<b>Power Requirements</b>	AC Input: 100-240 VAC, 50-60 Hz DC Input: 5-12 V USB-C Power Delivery (3650/3670): 9 or 12 V		
	All models, no auxiliary HandHeld device attached: Operating (Maximum): 3 Watts Operating (Nominal): 1.2 Watts Sleep Mode: 1.0 Watts		
<b>Power Consumption</b>	M3x50 and M3x70 only: with Auxiliary HandHeld device attached, 12V power source: Operating (Maximum): 6 Watts Operating (Nominal): 1.8 Watts Sleep Mode: 1.5 Watts (average values considering Datalogic QD2500 HandHeld scanner)		
ENVIRONMENTAL		Typical Depth of Field	
<b>Ambient Light</b>	0 to 86,100 lux		
<b>ESD Protection (Air Discharge)</b>	25 kV		
<b>Humidity (Non-Condensing)</b>	5 - 95%		
<b>Particulate and Water Sealing</b>	IP52		
<b>Temperature</b>	Operating: 0 to 40 °C / 50 to 104 °F Storage/Transport: -40 to 70 °C / -40 to 158 °F		
INTERFACES		READING PERFORMANCE	
<b>Interfaces</b>	OEM (IBM) USB; RS-232; USB Keyboard, USB Com	Graphic Formats: BMP, JPEG, TIFF, RAW Color(3650/3670) and Grayscale	
<b>Auxiliary Ports (3650/3670)</b>	Powered Type A USB (USB Com) Requires 12V Power Supply, 12V OEM-USB, or 9-12V USB-C Power Delivery	1360 x 1120 pixels, Global Shutter	
OPTIONAL FEATURES		Multiple diffused LEDs, orientation and wavelength optimized for eye comfort	
<b>EAS Features</b>	Checkpoint Systems: Integrated EAS hardware will work with Counterpoint IX and Evolve D11 models; Sensormatic: Good Read Acknowledgement		
<b>Value Added Features</b>	Diagnostic Reporting; Host Download; Magellan ULE Scripting		
PHYSICAL CHARACTERISTICS		Print Contrast Ratio (Minimum)	
<b>Dimensions</b>	13.7 x 15.2 x 8.4 cm / 5.4 x 6.0 x 3.3 in	25%	
<b>Weight</b>	0.60 kg / 1.3 lb		
RFID (AVAILABLE FOR 3650/3670)		Read Height	
<b>Standard</b>	EPC UHF Class 1 Gen 2 (ISO 18000-6C) Requires 12V Power Supply, 12V OEM-USB, or 9-12V USB-C Power Delivery	15.0 cm / 6.0 in (EAN 13 mils at 15cm distance)	
<b>Frequency</b>	US: 902 MHz to 928 MHz EU: 865 MHz to 868 MHz	Grayscale Read Rate (Maximum)	
<b>Modulation</b>	ASK (Amplitude Shift Keying)	60 Million pixels per second	
<b>Power</b>	Max 9dBm (configurable)	Color Image Read Rate (Maximum, 3650/3670)	
<b>Reading Range</b>	Up to 20 cm / 7.9 inch (linear)	4 seconds per image (JPEG format)	
COLOR VIDEO CAMERA (3670)		Reading Angle	
	Without White Illumination enabled: Operating: 0.5 Watts	Pitch: +/- 65°; Roll (Tilt): 0 - 360°; Skew (Yaw): +/- 65°	
	With White Illumination enabled: Operating (Maximum): 2.5 Watts Operating (Nominal): 0.8 Watts Sleep Mode: 0.5 Watts	Reading Indicators	
<b>Power Consumption (on dedicated USB 5V interface)</b>	1280 x 800 pixels, Global Shutter 40 frames per second 74°H x 50°V	Audio speaker with adjustable tone and volume; Good Read LED; Good Transmission	
<b>Resolution</b>	USB Type B Port (USB 2.0), USB Video Class (UVC) Protocol	Resolution (Maximum)	
<b>Framerate</b>		1D Codes: 3 mil 2D Codes: 6 mil	
<b>Field of View</b>		SAFETY & REGULATORY	
<b>Connectivity</b>		Agency Approvals	The product meets necessary safety and regulatory approvals for its intended use. The Quick Reference Guide for this product can be referred to for a complete list of certifications.
		Environmental Compliance	Complies to China RoHS; Complies to EU RoHS
		LED Classification	EN62471 and IEC62471 Lamp Illumination - Exempt Group
UTILITIES		WARRANTY	
<b>Aladdin</b>	Magellan Aladdin configuration software is available for download at <a href="http://www.datalogic.com">www.datalogic.com</a>	<b>Warranty</b>	3-Year Factory Warranty
<b>OPOS / JavaPOS</b>	JavaPOS Utilities are available for download at no charge. OPOS Utilities are available for download at no charge		

## ACCESSORIES

## Mounts/Stands



• 90ACC0598 Wall/Counter Mount



• 90ACC0599 Tilt/Riser Mount



• 90ACC0515 Customer Service Scanner with Omni Mount